

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification ⁷ : A47G 19/22, B65D 47/20, 51/16</p>	<p>A1</p>	<p>(11) International Publication Number: WO 00/28864 (43) International Publication Date: 25 May 2000 (25.05.00)</p>
<p>(21) International Application Number: PCT/NL99/00692 (22) International Filing Date: 12 November 1999 (12.11.99) (30) Priority Data: 1010555 13 November 1998 (13.11.98) NL (71)(72) Applicants and Inventors: VAN DE POL-KLEIN NAGELVOORT, Henriette, Hermine, Titia [NL/NL]; De Hulle 12, NL-7421 EC Deventer (NL). KLEIN NAGELVOORT, Jan, Albert, Henri [NL/NL]; Juliana van Stolberglaan 4, NL-6961 GD Eerbeek (NL). JEN-DEN-KLEIN NAGELVOORT, Alberthe, Joan [NL/NL]; P.A. Bernhardlaan 9, NL-6998 AS Laag-Keppel (NL). KLEIN NAGELVOORT, Henri, Jan, Albert [NL/NL]; Bernhardlaan 9, NL-6998 AS Laag-Keppel (NL). (74) Agent: DE BRUIJN, Leendert C. et al.; Nederlandsch Octrooibureau, P.O. Box 29720, Scheveningseweg 82, NL-2502 LS The Hague (NL).</p>		<p>(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report. In English translation (filed in Dutch).</p>

(54) Title: LEAK-FREE DRINKING BEAKER

(57) Abstract

A leak-free drinking beaker comprises a container (1) as well as a lid (2) closing the container (1), a drink opening (17) which opens into the interior of the container, and a valve (12) extending over the drink opening (17), which valve (12) is held in the closed position under a certain pretension and can be released against said pretension under the influence of a pressure difference. The valve (12) is a double-acting non-return valve and comprises a flexible valve element (12) and two separate valve seats (11, 16), the valve element (12) and one of the valve seats (11) have a blocking action in a direction opposed to the direction in which the valve element (12) has a blocking action with the other valve seat (16).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

Leak-free drinking beaker

The invention relates to a leak-free drinking beaker, comprising a container as well as a lid closing the container, a drink opening which opens into the interior of the container, and a valve, extending over the drink opening, between the drink opening
5 and the container, which valve is held in the closed position under a certain pretension and can be released against said pretension under the influence of a pressure difference.

A drinking beaker of this type is disclosed in WO-A 9708979. The valve used in said beaker is in the form of a membrane in which a slit has been made. When drinking,
10 the slit opens a little so that liquid flows from the drinking beaker. The disadvantage of this known drinking beaker is that the membrane does not seal well. If the drinking beakers falls over or is turned upside down, leakage can still occur as a result of the liquid pressure.

The aim of the invention is to provide a drinking beaker with which freedom
15 from leaks is better guaranteed. This is achieved in that the valve is a double-acting non-return valve, comprising a flexible valve element and two separate valve seats, the valve element and one of the valve seats having a blocking action in a direction opposed to the direction in which the valve element has a blocking action with the other valve seat.

20 By virtue of the use of a double-acting non-return valve it is possible, on the one hand, to ensure good sealing against leakage whilst, on the other hand, the reduced pressure produced in the drinking beaker by drinking can nevertheless be released. The air that flows in on equalising the reduced pressure can also carry liquid residues back into the beaker, as a result of which subsequent dripping is virtually precluded.

25 The flexible valve element can be constructed in various ways. According to a simple embodiment, the flexible valve element comprises an annular membrane, one peripheral rim of which interacts with the one valve seat and the other peripheral rim of which interacts with the other valve seat.

The membrane can be a disc which has a central hole, the one valve seat being
30 located opposite the one side of the disc at the outermost rim of the disc and the other valve seat being located opposite the other side of the disc at the innermost rim of the disc. Such a construction is simple and has the advantage that cleaning of the beaker and lid with valve can be carried out easily and reliably.

The two valve seats can be movable with respect to one another in the direction transverse to their plane to change the pretension under which the disc is in contact with the valve seats.

One of the valve seats is formed by that rim of a drinking spout which protrudes
5 inside the lid. The other valve seat is formed by a pin which is coaxial with respect to the other valve seat. With this arrangement the disc is located between the two valve seats and is held in place by the pin which extends to some extent into the interior opening of the disc.

Furthermore, the pin can be movable in the axial direction in order to vary the
10 preloading between disc and valve seats.

The pin is preferably accommodated on a support that is mounted in the lid. Said support can be slidably mounted in the lid in order to vary the mutual spacing of the valve seats and thus the pretension in the valve.

Preferably, the lid has a peripheral rim provided with a screw thread which
15 interacts with a corresponding screw thread on the container, the support being slidable in the axial direction in said peripheral rim. The support interacts with the upper limit of the container such that when the lid is screwed on to the container the pretension between the membrane and the valve seats is adjustable.

Depending on the drink used and/or on the user, it is always possible to set the
20 pretension such that, on the one hand, drinking remains possible, but leaking is prevented.

The peripheral rim has an axial extension which interacts with a sealing ring provided at the periphery of the container, which extension and sealing ring interact with one another over the entire screw region of the screw threads of lid and container.

25 The support is pretensioned in the direction towards the container.

The invention will be explained in more detail with reference to an illustrative embodiment shown in the figures.

Figures 1 and 2 show a cross-section through the leak-free drinking beaker according to the invention.

30 Figure 3 shows an exploded view in perspective.

Figures 4 - 6 show details of the drink opening with valve element.

Figures 7 - 8 show details of a variant.

The leak-free drinking beaker shown in Figures 1 and 2 comprises a container 1

and a lid 2 screwed thereon. A support 3 is also accommodated between the container 1 and the lid 2. Said support 3 on the one hand bears on the top rim 4 of the container 1 and, on the other hand, is pretensioned against the inside of the lid 2 by means of fingers 5 forming one piece with the support.

5 The lid 2 has an annular rim 6, on the inside of which a screw thread 7 has been produced. The container 1 is provided at the top with corresponding screw thread 8, on to which the screw thread 7 of lid 2 is screwed.

The support 3 has holes 9 via which the liquid is able to flow from the container 1 to the spout 10 arranged in the lid 2.

10 That part of the spout 10 that extends into the lid 2 has an annular rim 11 which forms a first valve seat for the valve element 12, which in the example shown is constructed as an annular membrane. The outermost rim of the disc 13 of the annular membrane 12 interacts with the first valve seat 11.

A pin 14 is provided on the support 3, which pin 14 is coaxial with respect to the rim of the spout 10 forming the valve seat 11. Said pin 14 forms the second valve seat, which interacts with the inside edge 15 of the central hole 20 in the annular membrane.

In the rest position the annular membrane 12 is in contact with both the first seat 11 and the second seat 16, determined by the surface of the pin 14. In this position the passage between the interior of the container 1 and the passage 17 in the spout 10 is blocked: see Figure 4.

However, as soon as, as is shown in Figure 5, a reduced pressure is generated in the passage 17, for example by sucking on it, the annular membrane 12 bulges slightly upwards, the rim 15 being lifted off the valve seat 16 determined by the pin 14. In this position the liquid is able to issue from the container 1 via the passage 17.

25 As soon as the reduced pressure is cancelled out, the rim 15 of the annular membrane 12 moves back on to the valve seat 16, as a result of which the passage is blocked again.

If a sufficiently high reduced pressure has been produced in the container 1, the outside edge 13 of the annular membrane 12 will then be lifted off the first valve seat 11, such that ambient air is able to flow into the container 1: see Figure 6. During this operation any liquid that has remained behind in the passage 17 is guided back into the container 1, together with the inflowing air. Consequently subsequent dripping of the spout 10 can be prevented.

The opening of the annular membrane 12 in both directions is dependent on the pretension under which the edges 13, 15 interact with the respective valve seats 11, 16. The pretension can be adjusted, as will be explained with reference to Figures 1 and 2.

5 In the position shown in Figure 1, the lid 2 has been screwed less far down on to the container 1, as a result of which the distance between the valve seats 11 and 16 in the vertical direction or in the direction of flow is relatively large. The annular membrane 12 will consequently be in contact with the valve seat under low pretension, as a result of which the membrane 12 opens easily.

10 In the position in Figure 2, the lid 2 has been screwed further down on to the container 1. As a result the membrane 12 is pressed more firmly on to the valve seats 11, 16, as can also be deduced from the deformed state of said membrane 12.

In this case a greater reduced pressure in the passage 17 of the spout 10 is needed to open the membrane 12. This adjustment facility is useful to be able to vary the suction under which the membrane 12 opens.

15 The seal between lid 2 and container 1 is always guaranteed by the extension 20, provided on rim 6, which interacts with sealing ring 21, which is accommodated in the top rim of the container 1.

20 In the variant shown in Figures 7 and 8, the valve element 12 can be accommodated between the rim 11 of the spout 10 and a cap 30, the annular rim 31 of which is fixed to the spout 10.

The base 32 of the cap has holes 33 and carries the pin 14. Said pin 14 forms the second valve seat; the rim 11 forms the first valve seat.

The embodiment in Figures 7 and 8 has a fixed setting of the valve element 12 and in other respects functions in the same way as the embodiment in Figures 1 - 6.

Claims

1. Leak-free drinking beaker, comprising a container (1) as well as a lid (2) closing the container (1), a drink opening (17) which opens into the interior of the container, and a valve (12) extending over the drink opening (17), which valve (12) is held in the closed position under a certain pretension and can be released against said pretension under the influence of a pressure difference, characterised in that the valve is a double-acting non-return valve, comprising a flexible valve element (12) and two separate valve seats (11, 16), the valve element (12) and one of the valve seats having a blocking action in a direction opposed to the direction in which the valve element (12) has a blocking action with the other valve seat (16).

2. Drinking beaker according to Claim 1, wherein the flexible valve element comprises an annular membrane (12), one peripheral rim (13) of which interacts with the one valve seat (11) and the other peripheral rim (15) of which interacts with the other valve seat (16).

3. Drinking beaker according to Claim 1, wherein the membrane (12) is a disc which has a central hole (20), the one valve seat (11) is located opposite the one side of the disc (12) at the outermost rim (13) of the disc and the other valve seat (16) is located opposite the other side (12) of the disc at the innermost rim (15) of the disc.

4. Drinking beaker according to Claim 3, wherein the two valve seats (11, 16) are movable with respect to one another in the direction transverse to their plane to change the pretension under which the disc (12) is in contact with the valve seats (11, 16).

5. Drinking beaker according to Claim 4, wherein one of the valve seats (11) is formed by that rim of a drinking spout (10) which protrudes inside the lid.

6. Drinking beaker according to Claim 4 or 5, wherein one of the valve seats (16) is formed by a pin (14) which is coaxial with respect to the other valve seat (11).

7. Drinking beaker according to Claims 5 and 6, wherein the disc (12) is located

between the two valve seats (11, 16) and the pin (14) extends into the central hole (20) of the disc (12) in order to hold this in place between the valve seats (11, 16).

8. Drinking beaker according to Claim 7, wherein the pin (14) is movable in the axial direction in order to vary the preloading between disc and valve seats (11, 16).

9. Drinking beaker according to Claim 8, wherein the pin (14) is accommodated on a support (3) that is mounted in the lid (2).

10. Drinking beaker according to Claim 9, wherein the support (3) is slidable with respect to the lid (2) in order to vary the mutual spacing of the valve seats (11, 16).

11. Drinking beaker according to Claim 10, wherein the lid (2) has a peripheral rim (6) provided with a screw thread (7) which interacts with a corresponding screw thread (8) on the container (1), the support (3) being slidable in the axial direction in said peripheral rim (6), and the support (3) interacts with the upper limit (4) of the container (1) such that when the lid (2) is screwed on to the container (1) the distance, and hence the pretension, between the membrane (12) and the valve seats (11, 16) is adjustable.

12. Drinking beaker according to Claim 11, wherein the peripheral rim (6) has an axial extension (22) which interacts with a sealing ring (21) provided at the periphery of the container (1), which extension (22) and sealing ring (21) interact with one another over the entire screw region of the screw threads (7, 8) of lid (2) and container (1).

13. Drinking beaker according to Claim 9, 10, 11 or 12, wherein the support (3) is pretensioned (5) in the direction towards the container (1).

fig-1

fig-2





fig - 3




fig - 4




fig - 5




fig - 6




fig- 7





fig- 8



INTERNATIONAL SEARCH REPORT

Int. oral Application No
PCT/NL 99/00692

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A47G19/22 B65D47/20 B65D51/16

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A47G B65D A61J

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, X	WO 99 38423 A (CANNON RUBBER LTD ; ATKIN EDWARD (GB); WILLIAMS ROGER LEONARD (GB)) 5 August 1999 (1999-08-05) page 6, line 8 -page 17, line 20; figures	1-3
A	GB 2 266 045 A (HABERMAN MANDY NICOLA) 20 October 1993 (1993-10-20) page 6, paragraph 2 -page 8, paragraph 1; figures 1,2	1
A	IT 594 286 A (MUTTI ET AL) 30 May 1959 (1959-05-30)	
A	US 5 542 670 A (MORANO EMANUEL P) 6 August 1996 (1996-08-06)	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

19 January 2000

Date of mailing of the international search report

24/02/2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 851 epo nl,
Fax: (+31-70) 340-3018

Authorized officer

Vistisen, L

INTERNATIONAL SEARCH REPORT

Information on patent family members

Initial Application No

PCT/NL 99/00692

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9938423 A	05-08-1999	AU 2291399 A GB 2333770 A	16-08-1999 04-08-1999
GB 2266045 A	20-10-1993	DE 69319109 D DE 69319109 T EP 0634922 A ES 2117707 T WO 9319718 A HK 1007675 A	16-07-1998 24-12-1998 25-01-1995 16-08-1998 14-10-1993 23-04-1999
IT 594286 A		NONE	
US 5542670 A	06-08-1996	AU 6316296 A CA 2227186 A EP 0909137 A WO 9703594 A JP 11509125 T NZ 311775 A	18-02-1997 06-02-1997 21-04-1999 06-02-1997 17-08-1999 28-10-1999